



**R 20**



**BR 30**



**BR 40**

Set the mood with QLS BR lamps. A wide range of color temperatures and wattages give you the flexibility to design your perfect space. Our BR Lamps provide exceptional dimming that allows for ideal lighting any time of day. These cost efficient and durable lamps match the style of incandescents and can be used in a wide variety of applications.

### FEATURES

- Sturdy, plastic and aluminum design
- Smooth, even, light distribution
- Dimmable to 0%
- Damp and enclosed location rated
- Life: L70 25,000 Hours
- 50/65/85/100 watt equivalent

### APPLICATIONS

This product family can be effectively used in downlight, floodlight, and close spotlight applications. Commercial, industrial, retail, residential and healthcare applications.

### ITEM NUMBER GUIDE ex. LR40D10030E

Family	Size	Dim-mable	Watt	CCT	Energy Star
LR	20	D	50	27	E
	30		85	30	
	40		100	40	
				50	

↓ ↓ ↓ ↓ ↓ ↓  
LR 40 D 100 30 E

## R 20 - E26 Base 120V



QLS	Watt.	Lumens	Eff L/W	P.F.	Dim.	CCT	CRI	Case QTY	Watt. Equiv.	Life	H (In)	W (In)	Energy Star
LR20D5027E	7.0	525	75	≥0.8	Yes	2700	>83	48	50	25000	3.8	2.5	Yes
LR20D5030E	7.0	525	75	≥0.8	Yes	3000	>83	48	50	25000	3.8	2.5	Yes
LR20D5040E	7.0	525	75	≥0.8	Yes	4000	>83	48	50	25000	3.8	2.5	Yes
LR20D5050E	7.0	525	75	≥0.8	Yes	5000	>83	48	50	25000	3.8	2.5	Yes

## BR 30 - E26 Base 120V



QLS	Watt.	Lumens	Eff L/W	P.F.	Dim.	CCT	CRI	Case QTY	Watt. Equiv.	Life	H (In)	W (In)	Energy Star
LR30D6527E	8.0	650	76.5	≥0.9	Yes	2700	>83	48	65	25000	5.3	3.7	Yes
LR30D6530E	8.0	650	76.5	≥0.9	Yes	3000	>83	48	65	25000	5.3	3.7	Yes
LR30D6540E	8.0	650	76.5	≥0.9	Yes	4000	>83	48	65	25000	5.3	3.7	Yes
LR30D6550E	8.0	650	76.5	≥0.9	Yes	5000	>83	48	65	25000	5.3	3.7	Yes
LR30D8527E	13.0	1064	81.8	≥0.9	Yes	2700	>83	48	85	25000	5.3	3.7	Yes
LR30D8530E	13.0	1064	81.8	≥0.9	Yes	3000	>83	48	85	25000	5.3	3.7	Yes
LR30D8540E	13.0	1064	81.8	≥0.9	Yes	4000	>83	48	85	25000	5.3	3.7	Yes
LR30D8550E	13.0	1064	81.8	≥0.9	Yes	5000	>83	48	85	25000	5.3	3.7	Yes

## BR 40 - E26 Base 120V



QLS	Watt.	Lumens	Eff L/W	P.F.	Dim.	CCT	CRI	Case QTY	Watt. Equiv.	Life	H (In)	W (In)	Energy Star
LR40D8527E	14.0	1064	76	≥0.9	Yes	2700	>80	24	85	25000	6.0	5.0	Yes
LR40D8530E	14.0	1064	76	≥0.9	Yes	3000	>80	24	85	25000	6.0	5.0	Yes
LR40D8540E	14.0	1064	76	≥0.9	Yes	4000	>80	24	85	25000	6.0	5.0	Yes
LR40D8550E	14.0	1064	76	≥0.9	Yes	5000	>80	24	85	25000	6.0	5.0	Yes
LR40D10027E	17.0	1250	74	≥0.9	Yes	2700	>80	24	100	25000	6.0	5.0	
LR40D10030E	17.0	1250	74	≥0.9	Yes	3000	>80	24	100	25000	6.0	5.0	
LR40D10040E	17.0	1250	74	≥0.9	Yes	4000	>80	24	100	25000	6.0	5.0	
LR40D10050E	17.0	1250	74	≥0.9	Yes	5000	>80	24	100	25000	6.0	5.0	