

## Features

- Rugged construction
- Made to retrofit into existing exit signs for maximum energy efficiency
- Unit has a patented swivel base that allows for perfect positioning in the exit sign
- Made to UL 924 Specifications
- UL/cUL Listed
- Innovative high brightness LEDs produce crisp, even light without shadows or hot spots
- Directs light output where you need it the most in existing exit signs!
- For use with 120V only
- Life expectancy 10 years at full lumen output
- Diffuser panels may be field cut to smaller dimensions to fit into existing exit signs



## Ordering Information

Catalog Model #	Description	M.O.L. (Inches)	Diameter (Inches)	Power Factor	Input Voltage	Watts Per Lamp
20710	One Red LED Lamp, Candelabra Base	4.70"	1.25"	>.57"	120V	0.7W
20711	One Red LED Lamp, Candel. Base, 2 Adapt.	4.70"	1.25"	>.57"	120V	0.7W
20714	Two Red LED Lamps, Candel. Base, 4 Adapt.	4.70"	1.25"	>.57"	120V	0.7W
20720	Two Red LED Lamps, Candel. Base, 4 Adapt. Plus Red Diffuser Panel.	4.70"	1.25"	>.57"	120V	0.7W
20799	Socket Adaptor Candelabra to Bayonet Base	1.00"	0.50"	-	-	-
20798	Socket Adaptor Candelabra to Intermediate	1.00"	0.50"	-	-	-
20797	Socket Adaptor Candelabra to Medium Base	1.00"	0.50"	-	-	-
29999	Red Diffuser Panel	8.25"	13.0"	-	-	-
29999G	Green Diffuser Panel	8.25"	13.0"	-	-	-

