Industra by ØTCP

Wrap Light

The TCP Wrap Light offers superior light output in a maintenance free fixture. With a durable metal frame, and a glare free, impact resistant frosted lens, you can install these fixtures and relax. Built to industry standard measurements, installation is quick and easy, and provides for easy upgrading.

Great Features/Benefits

- Energy efficient Up to 56% • energy savings compared to HID
- Smooth, uniform dimming (O-10V)
- Instant on, no warm up time for full light
- Long life: 50,000 hours ٠
- Replaces traditional metal • halideand linear fluorescent systems
- Heavy duty steel housing





5 YEAR WARRANTY

we know light.™

Ideal for:

3

- Warehouses & **Distribution Centers**
- **Commercial Facilities**
- Aisles (Open & Stock)
- Restrooms
- Corridors
- Stairwells Hallways



LED Wrap Light

Applications

The TCP Wrap Light offers superior light output in a maintenance free fixture. With a durable metal frame, and a glare free, impact resistant lens, you can install these fixtures and relax. Built to industry standard measurements, installation is quick and easy, and provides for easy upgrading.

Construction

- Housing: durable steel construction
- Finish: powder coated, post-painted white
- Large wiring compartment and multiple knock-outs to accommodate lighting controls

Electrical

- cULus damp location rated
- 0-10V dimming driver (standard)
- Easy-to-access wiring compartment
- System rated for long 50,000 hour life
- Efficiently delivers >110 LPVV

Optics

- High impact, acrylic lens comes standard to protect the LEDs and minimize glare
- Delivers bright, white light and excellent uniformity



UL and cUL listed RoHS Compliant DLC v4.3 Standard

Five year limited warranty against defects in manufacturing.









To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/qpl

ITEM #	DESCRIPTION	DLC	LUMENS	WATTAGE	LPW	VOLTAGE	POWER FACTOR	ССТ	CRI	LIFE	L (inches)	H (inches)	W (inches)
LED Wrap Light • Dimmable • 50,000 Hour													
LVVR4000	0135 LED Wrap Light - 35K	*	4700	40	118	120V-277v AC	≥0.9	3500K	80	50000	47.7	7.1	2.8
LVVR4000	0140 LED Wrap Light - 40K	*	4750	40	119	120V-277v AC	≥0.9	4000K	80	50000	47.7	7.1	2.8
LVVR4000	0150 LED Wrap Light - 50K	*	4850	40	121	120V-277v AC	≥0.9	5000K	80	50000	47.7	7.1	2.8
LVVR6300	0135 LED Wrap Light - 35K	*	7700	63	121	120V-277v AC	≥0.9	3500K	80	50000	47.7	7.1	2.8
LVVR6300	0140 LED Wrap Light - 40K	*	7900	63	125	120V-277v AC	≥0.9	4000K	80	50000	47.7	7.1	2.8
LVVR6300	0150 LED Wrap Light - 50K	*	8050	63	125	120V-277v AC	≥0.9	5000K	80	50000	47.7	7.1	2.8

For the most up-to-date specs and warranty information, please visit www.tcpi.com