



LED G4

Base Lamps

Product Specifications



These energy efficient lamps are the perfect solution for replacing Halogen G4 based lamps. They are ideal for a variety of landscape, under-cabinet, and decorative lighting applications.

Reasons to choose LED Elevator Lamps from TCP

- Over 50% in energy savings compared to halogen
- 25,000 hours rated life with a 5 year warranty
- Suitable for enclosed fixtures, making it perfect for outdoor applications
- Contains no lead or mercury, making environmentally safe disposal easy
- 360° of light output and can be used in vertical or horizontal applications

Ideal Applications

- Landscape lighting
- Bath lights
- Pathway lighting
- Under-cabinet lighting applications

Specifications

Voltage 12V
Input Line Frequency..... 50/60Hz
Lamp Life (Rated) 25,000 hours
Minimum Starting Temp -20°F/-28.9°C

Maximum Operating Temp..... 104°F/40°C
Dimmable Yes
Warranty 5 Years

Specifications

Item #	Description	Pack	Voltage	Watts	Lumens	Color	Hours	CRI	MOL	DIA	Base	Warranty	Case Qty
LT100G4D27K	LED G4 Base 100L Dim 27K	2	12V	1	100	2700K	25,000	90	1.31	0.44	G4	5 Years	12
LT100G4D30K	LED G4 Base 100L Dim 30K	2	12V	1	100	3000K	25,000	90	1.31	0.44	G4	5 Years	12
LT100G4D50K	LED G4 Base 100L Dim 50K	2	12V	1	100	5000K	25,000	90	1.31	0.44	G4	5 Years	12
LT150G4D27K	LED G4 Base 150L Dim 27K	2	12V	1.5	150	2700K	25,000	90	1.38	0.5	G4	5 Years	12
LT150G4D30K	LED G4 Base 150L Dim 30K	2	12V	1.5	150	3000K	25,000	90	1.38	0.5	G4	5 Years	12
LT150G4D50K	LED G4 Base 150L Dim 50K	2	12V	1.5	150	5000K	25,000	90	1.38	0.5	G4	5 Years	12
LT200G4D27K	LED G4 Base 200L Dim 27K	2	12V	2	200	2700K	25,000	90	1.38	0.56	G4	5 Years	12
LT200G4D30K	LED G4 Base 200L Dim 30K	2	12V	2	200	3000K	25,000	90	1.38	0.56	G4	5 Years	12
LT200G4D50K	LED G4 Base 200L Dim 50K	2	12V	2	200	5000K	25,000	90	1.38	0.56	G4	5 Years	12
LT250G4D27K	LED G4 Base 250L Dim 27K	2	12V	2.5	250	2700K	25,000	90	1.25	0.63	G4	5 Years	12
LT250G4D30K	LED G4 Base 250L Dim 30K	2	12V	2.5	250	3000K	25,000	90	1.25	0.63	G4	5 Years	12
LT250G4D50K	LED G4 Base 250L Dim 50K	2	12V	2.5	250	5000K	25,000	90	1.25	0.63	G4	5 Years	12
LT300G4D27K	LED G4 Base 300L Dim 27K	2	12V	3	300	2700K	25,000	90	1.63	0.69	G4	5 Years	12
LT300G4D30K	LED G4 Base 300L Dim 30K	2	12V	3	300	3000K	25,000	90	1.63	0.69	G4	5 Years	12
LT300G4D50K	LED G4 Base 300L Dim 50K	2	12V	3	300	5000K	25,000	90	1.63	0.69	G4	5 Years	12
LT425G4D27K	LED G4 Base 425L Dim 27K	2	12V	4	425	2700K	25,000	90	1.88	0.69	G4	5 Years	12
LT425G4D30K	LED G4 Base 425L Dim 30K	2	12V	4	425	3000K	25,000	90	1.88	0.69	G4	5 Years	12
LT425G4D50K	LED G4 Base 425L Dim 50K	2	12V	4	425	5000K	25,000	90	1.88	0.69	G4	5 Years	12
LT550G4D27K	LED G4 Base 550L Dim 27K	2	12V	5	550	2700K	25,000	90	2	0.81	G4	5 Years	12
LT550G4D30K	LED G4 Base 550L Dim 30K	2	12V	5	550	3000K	25,000	90	2	0.81	G4	5 Years	12
LT550G4D50K	LED G4 Base 550L Dim 50K	2	12V	5	550	5000K	25,000	90	2	0.81	G4	5 Years	12