



LED Classic Decorative Filament Lamps

Product Specifications



TCP's filament style LED decorative lamps create a relaxing atmosphere with decorative touches that light up the room. Exclusive LED technology provides unmatched longevity and perfect 5-100% dimming.

Reasons to choose the LED Classic Decorative Filament Lamps from TCP

- Smooth, uniform dimming from 5 – 100%
- Energy efficient — uses up to 85% less energy than halogen lamps
- UL approved for damp and enclosed locations means the lamps can be used outdoors when protected from the elements and withstand humidity indoors and outdoors
- Low heat generation minimizes replacement and maintenance costs
- Long life —15,000 hours rated life
- Unique filament LED configuration provides uniform color output
- ANSI construction compliant means lamps fit most general applications

Ideal Applications

- Accent Lighting
- Chandeliers
- Wall Sconces
- Ceiling Fans
- Decorative Lighting

Specifications

| | | | |
|----------------------------|-----------------------------------|------------------------------|---------|
| Color Temperatures | 2200K, 2700K, 3000K, 4000K, 5000K | Minimum Starting Temp | -30°C |
| Input Line Voltage | 120 VAC | Maximum Operating Temp | 40°C |
| Input Line Frequency | 50/60HZ | CRI | >80 |
| Lamp Life (Rated) | 15,000 hours | Base | E12/E26 |



Specifications



| ITEM # | DESCRIPTION | LED WATTS | INCAND. WATTS | LUMENS | CRI | COLOR TEMP | GLASS TYPE | MOL (inches) | DIA (inches) | BASE |
|---|---------------------------|-----------|---------------|--------|-----|------------|------------|--------------|--------------|------|
| B11 Lamps | | | | | | | | | | |
| 25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour | | | | | | | | | | |
| FB11D2522KE12C | B11 25W 2200K CLEAR E12 | 3.0 | 25 | 225 | >80 | 2200K | Clear | 3.8 | 1.4 | E12 |
| FB11D2522KE12G | B11 25W 2200K AMBER E12 | 3.0 | 25 | 225 | >80 | 2200K | Amber | 3.8 | 1.4 | E12 |
| FB11D2522KE12W | B11 25W 2200K FROSTED E12 | 3.0 | 25 | 225 | >80 | 2200K | Frosted | 3.8 | 1.4 | E12 |
| FB11D2527EE12C | B11 25W 2700K CLEAR E12 | 3.0 | 25 | 250 | >80 | 2700K | Clear | 3.8 | 1.4 | E12 |
| FB11D2527EE12W | B11 25W 2700K FROSTED E12 | 3.0 | 25 | 250 | >80 | 2700K | Frosted | 3.8 | 1.4 | E12 |
| FB11D2527KE12G | B11 25W 2700K AMBER E12 | 3.0 | 25 | 250 | >80 | 2700K | Amber | 3.8 | 1.4 | E12 |
| FB11D2530EE12C | B11 25W 3000K CLEAR E12 | 3.0 | 25 | 250 | >80 | 3000K | Clear | 3.8 | 1.4 | E12 |
| FB11D2540EE12C | B11 25W 4000K CLEAR E12 | 3.0 | 25 | 250 | >80 | 4000K | Clear | 3.8 | 1.4 | E12 |
| FB11D2550EE12C | B11 25W 5000K CLEAR E12 | 3.0 | 25 | 250 | >80 | 5000K | Clear | 3.8 | 1.4 | E12 |
| FB11D2550EE12W | B11 25W 5000K FROSTED E12 | 3.0 | 25 | 250 | >80 | 5000K | Frosted | 3.8 | 1.4 | E12 |
| 25 Watt Replacements • Dimmable • E26 Base • 15,000 Hour | | | | | | | | | | |
| FB11D2522KC | B11 25W 2200K CLEAR | 3.0 | 25 | 225 | >80 | 2200K | Clear | 3.5 | 1.4 | E26 |
| FB11D2522KW | B11 25W 2200K FROSTED | 3.0 | 25 | 225 | >80 | 2200K | Frosted | 3.5 | 1.4 | E26 |
| FB11D2527EC | B11 25W 2700K CLEAR | 3.0 | 25 | 250 | >80 | 2700K | Clear | 3.5 | 1.4 | E26 |
| FB11D2527EW | B11 25W 2700K FROSTED | 3.0 | 25 | 250 | >80 | 2700K | Frosted | 3.5 | 1.4 | E26 |
| FB11D2550EC | B11 25W 5000K CLEAR | 3.0 | 25 | 250 | >80 | 5000K | Clear | 3.5 | 1.4 | E26 |
| FB11D2550EW | B11 25W 5000K FROSTED | 3.0 | 25 | 250 | >80 | 5000K | Frosted | 3.5 | 1.4 | E26 |
| 40 Watt Replacements • Dimmable • E12 Base • 15,000 Hour | | | | | | | | | | |
| FB11D4022KE12C | B11 40W 2200K CLEAR E12 | 4.0 | 40 | 300 | >80 | 2200K | Clear | 3.8 | 1.4 | E12 |
| FB11D4022KE12G | B11 40W 2200K AMBER E12 | 4.0 | 40 | 300 | >80 | 2200K | Amber | 3.8 | 1.4 | E12 |
| FB11D4022KE12W | B11 40W 2200K FROSTED E12 | 4.0 | 40 | 300 | >80 | 2200K | Frosted | 3.8 | 1.4 | E12 |
| FB11D4027EE12C | B11 40W 2700K CLEAR E12 | 4.0 | 40 | 300 | >80 | 2700K | Clear | 3.8 | 1.4 | E12 |
| FB11D4027EE12W | B11 40W 2700K FROSTED E12 | 4.0 | 40 | 300 | >80 | 2700K | Frosted | 3.8 | 1.4 | E12 |
| FB11D4027EE12CB | B11 40W 2700K CLEAR E12 | 4.0 | 40 | 300 | >80 | 2700K | Clear | 3.8 | 1.4 | E12 |
| FB11D4030EE12C | B11 40W 3000K CLEAR E12 | 4.0 | 40 | 300 | >80 | 3000K | Clear | 3.8 | 1.4 | E12 |
| FB11D4040EE12C | B11 40W 4000K CLEAR E12 | 4.0 | 40 | 300 | >80 | 4000K | Clear | 3.8 | 1.4 | E12 |
| FB11D4050EE12C | B11 40W 5000K CLEAR E12 | 4.0 | 40 | 300 | >80 | 5000K | Clear | 3.8 | 1.4 | E12 |
| FB11D4050EE12W | B11 40W 5000K FROSTED E12 | 4.0 | 40 | 300 | >80 | 5000K | Frosted | 3.8 | 1.4 | E12 |



LED Classic Decorative Filament Lamps

Specifications

| ITEM # | DESCRIPTION | LED WATTS | INCAND. WATTS | LUMENS | CRI | COLOR TEMP | GLASS TYPE | MOL (inches) | DIA (inches) | BASE |
|---|---------------------------|-----------|---------------|--------|-----|------------|------------|--------------|--------------|------|
| B11 Lamps (continued) | | | | | | | | | | |
| 40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour | | | | | | | | | | |
| FB11D4022KC | B11 40W 2200K CLEAR | 4.0 | 40 | 295 | >80 | 2200K | Clear | 3.5 | 1.4 | E26 |
| FB11D4022KW | B11 40W 2200K FROSTED | 4.0 | 40 | 295 | >80 | 2200K | Frosted | 3.5 | 1.4 | E26 |
| FB11D4027EC | B11 40W 2700K CLEAR | 4.0 | 40 | 300 | >80 | 2700K | Clear | 3.5 | 1.4 | E26 |
| FB11D4027EW | B11 40W 2700K FROSTED | 4.0 | 40 | 300 | >80 | 2700K | Frosted | 3.5 | 1.4 | E26 |
| FB11D4050EC | B11 40W 5000K CLEAR | 4.0 | 40 | 300 | >80 | 5000K | Clear | 3.5 | 1.4 | E26 |
| FB11D4050EW | B11 40W 5000K FROSTED | 4.0 | 40 | 300 | >80 | 5000K | Frosted | 3.5 | 1.4 | E26 |
| 60 Watt Replacements • Dimmable • E12 Base • 15,000 Hour | | | | | | | | | | |
| FB11D6022EE12CS | B11 60W 2200K CLEAR E12 | 5.0 | 60 | 500 | >80 | 2200K | Clear | 4.1 | 1.4 | E12 |
| FB11D6027EE12CS | B11 60W 2700K CLEAR E12 | 5.5 | 60 | 500 | >80 | 2700K | Clear | 4.1 | 1.4 | E12 |
| FB11D6027EE12W | B11 60W 2700K FROST E12 | 5.0 | 60 | 500 | >80 | 2700K | Frosted | 4.1 | 1.4 | E12 |
| FB11D6030EE12CS | B11 60W 3000K CLEAR E12 | 5.0 | 60 | 500 | >80 | 3000K | Clear | 4.1 | 1.4 | E12 |
| FB11D6040EE12CS | B11 60W 4000K CLEAR E12 | 5.0 | 60 | 500 | >80 | 4000K | Clear | 4.1 | 1.4 | E12 |
| FB11D6050EE12CS | B11 60W 5000K CLEAR E12 | 5.0 | 60 | 500 | >80 | 5000K | Clear | 4.1 | 1.4 | E12 |
| FB11D6050EE12W | B11 60W 5000K FROST E12 | 5.0 | 60 | 500 | >80 | 5000K | Frosted | 4.1 | 1.4 | E12 |
| 60 Watt Replacements • Dimmable • E26 Base • 15,000 Hour | | | | | | | | | | |
| FB11D6022KC | B11 60W 2200K CLEAR | 5.0 | 60 | 475 | >80 | 2200K | Clear | 3.8 | 1.4 | E26 |
| FB11D6022KW | B11 60W 2200K FROSTED | 5.0 | 60 | 475 | >80 | 2200K | Frosted | 3.8 | 1.4 | E26 |
| FB11D6027EC | B11 60W 2700K CLEAR | 5.0 | 60 | 500 | >80 | 2700K | Clear | 3.8 | 1.4 | E26 |
| FB11D6027EW | B11 60W 2700K FROSTED | 5.0 | 60 | 500 | >80 | 2700K | Frosted | 3.8 | 1.4 | E26 |
| FB11D6050EC | B11 60W 5000K CLEAR | 5.0 | 60 | 500 | >80 | 5000K | Clear | 3.8 | 1.4 | E26 |
| FB11D6050EW | B11 60W 5000K FROSTED | 5.0 | 60 | 500 | >80 | 5000K | Frosted | 3.8 | 1.4 | E26 |
| F11 Lamps | | | | | | | | | | |
| 25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour | | | | | | | | | | |
| FF11D2522KE12C | F11 25W 2200K CLEAR E12 | 3.0 | 25 | 225 | >80 | 2200K | Clear | 3.8 | 1.4 | E12 |
| FF11D2522KE12W | F11 25W 2200K FROSTED E12 | 3.0 | 25 | 225 | >80 | 2200K | Frosted | 3.8 | 1.4 | E12 |
| FF11D2527EE12C | F11 25W 2700K CLEAR E12 | 3.0 | 25 | 220 | >80 | 2700K | Clear | 3.8 | 1.4 | E12 |
| FF11D2527EE12W | F11 25W 2700K FROSTED E12 | 3.0 | 25 | 250 | >80 | 2700K | Frosted | 3.8 | 1.4 | E12 |
| FF11D2530EE12C | F11 25W 3000K CLEAR E12 | 3.0 | 25 | 250 | >80 | 3000K | Clear | 3.8 | 1.4 | E12 |
| FF11D2540EE12C | F11 25W 4000K CLEAR E12 | 3.0 | 25 | 250 | >80 | 4000K | Clear | 3.8 | 1.4 | E12 |
| FF11D2550EE12C | F11 25W 5000K CLEAR E12 | 3.0 | 25 | 250 | >80 | 5000K | Clear | 3.8 | 1.4 | E12 |
| FF11D2550EE12W | F11 25W 5000K FROSTED E12 | 3.0 | 25 | 250 | >80 | 5000K | Frosted | 3.8 | 1.4 | E12 |
| 25 Watt Replacements • Dimmable • E26 Base • 15,000 Hour | | | | | | | | | | |
| FF11D2522KC | F11 25W 2200K CLEAR | 3.0 | 25 | 225 | >80 | 2200K | Clear | 3.6 | 1.4 | E26 |
| FF11D2522KW | F11 25W 2200K FROSTED | 3.0 | 25 | 225 | >80 | 2200K | Frosted | 3.6 | 1.4 | E26 |
| FF11D2527EC | F11 25W 2700K CLEAR | 3.0 | 25 | 250 | >80 | 2700K | Clear | 3.6 | 1.4 | E26 |
| FF11D2527EW | F11 25W 2700K FROSTED | 3.0 | 25 | 250 | >80 | 2700K | Frosted | 3.6 | 1.4 | E26 |
| FF11D2550EC | F11 25W 5000K CLEAR | 3.0 | 25 | 250 | >80 | 5000K | Clear | 3.6 | 1.4 | E26 |
| FF11D2550EW | F11 25W 5000K FROSTED | 3.0 | 25 | 250 | >80 | 5000K | Frosted | 3.6 | 1.4 | E26 |



Specifications

| ITEM # | DESCRIPTION | LED WATTS | INCAND. WATTS | LUMENS | CRI | COLOR TEMP | GLASS TYPE | MOL (inches) | DIA (inches) | BASE |
|---|---------------------------|-----------|---------------|--------|-----|------------|------------|--------------|--------------|------|
| F11 Lamps (continued) | | | | | | | | | | |
| 40 Watt Replacements • Dimmable • E12 Base • 15,000 Hour | | | | | | | | | | |
| FF11D4022KE12C | F11 40W 2200K CLEAR E12 | 4.0 | 40 | 300 | >80 | 2200K | Clear | 4.3 | 1.4 | E12 |
| FF11D4027EE12C | F11 40W 2700K CLEAR E12 | 4.0 | 40 | 300 | >80 | 2700K | Clear | 4.3 | 1.4 | E12 |
| FF11D4027EE12W | F11 40W 2700K FROSTED E12 | 4.0 | 40 | 300 | >80 | 2700K | Frosted | 4.3 | 1.4 | E12 |
| FF11D4030EE12C | F11 40W 3000K CLEAR E12 | 4.0 | 40 | 300 | >80 | 3000K | Clear | 4.3 | 1.4 | E12 |
| FF11D4040EE12C | F11 40W 4000K CLEAR E12 | 4.0 | 40 | 300 | >80 | 4000K | Clear | 4.3 | 1.4 | E12 |
| FF11D4050EE12C | F11 40W 5000K CLEAR E12 | 4.0 | 40 | 300 | >80 | 5000K | Clear | 4.3 | 1.4 | E12 |
| FF11D4050EE12W | F11 40W 5000K FROSTED E12 | 4.0 | 40 | 300 | >80 | 5000K | Frosted | 4.3 | 1.4 | E12 |
| 40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour | | | | | | | | | | |
| FF11D4027EC | F11 40W 2700K CLEAR | 4.0 | 40 | 300 | >80 | 2700K | Clear | 3.9 | 1.4 | E26 |
| FF11D4027EW | F11 40W 2700K FROSTED | 4.0 | 40 | 300 | >80 | 2700K | Frosted | 3.9 | 1.4 | E26 |
| FF11D4050EC | F11 40W 5000K CLEAR | 4.0 | 40 | 300 | >80 | 5000K | Clear | 3.9 | 1.4 | E26 |
| FF11D4050EW | F11 40W 5000K FROSTED | 4.0 | 40 | 300 | >80 | 5000K | Frosted | 3.9 | 1.4 | E26 |
| 60 Watt Replacements • Dimmable • E12 Base • 15,000 Hour | | | | | | | | | | |
| FF11D6027EE12C | F11 60W 2700K CLEAR E12 | 5.0 | 60 | 500 | >80 | 2700K | Clear | 4.3 | 1.4 | E12 |
| FF11D6027EE12W | F11 60W 2700K FROST E12 | 5.0 | 60 | 500 | >80 | 2700K | Frosted | 4.3 | 1.4 | E12 |
| FF11D6030EE12C | F11 60W 3000K CLEAR E12 | 5.0 | 60 | 500 | >80 | 3000K | Clear | 4.3 | 1.4 | E12 |
| FF11D6050EE12C | F11 60W 5000K CLEAR E12 | 5.0 | 60 | 500 | >80 | 5000K | Clear | 4.3 | 1.4 | E12 |
| 60 Watt Replacements • Dimmable • E26 Base • 15,000 Hour | | | | | | | | | | |
| FF11D6022KC | F11 60W 2200K CLEAR | 5.0 | 60 | 475 | >80 | 2200K | Clear | 4.1 | 1.4 | E26 |
| FF11D6022KW | F11 60W 2200K FROSTED | 5.0 | 60 | 475 | >80 | 2200K | Frosted | 4.1 | 1.4 | E26 |
| FF11D6027EC | F11 60W 2700K CLEAR | 5.0 | 60 | 500 | >80 | 2700K | Clear | 4.1 | 1.4 | E26 |
| FF11D6027EW | F11 60W 2700K FROSTED | 5.0 | 60 | 500 | >80 | 2700K | Frosted | 4.1 | 1.4 | E26 |
| FF11D6050EC | F11 60W 5000K CLEAR | 5.0 | 60 | 500 | >80 | 5000K | Clear | 4.1 | 1.4 | E26 |
| FF11D6050EW | F11 60W 5000K FROSTED | 5.0 | 60 | 500 | >80 | 5000K | Frosted | 4.1 | 1.4 | E26 |

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516