



Hi CRI LED Filament Lamps

Dimmable
Omnidirectional
15,000 Hours



TCP's High CRI LED Filament line provides outstanding color consistency and rendering combined with the filament elegance and uniformed light output.

Reasons to choose the Hi CRI LED Filament Lamps from TCP

- High R9 value provides excellent color rendering results and color consistency while maintaining uniformity
- Energy savings of up to 80% less energy than halogen alternatives
- Unique appearance - LED configuration provides a uniform color output
- Long lasting, minimalizing replacement and maintenance costs
- Smooth, uniform dimming
- UL approved for damp and enclosed locations



Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Recessed Lighting

Specifications:

Color Temperatures.....2400K, 2700K, 3000K,
4000K, 5000K
 Input Line Voltage 120 VAC Input Line
 Frequency 50/60HZ
 Lamp Life (Rated) 15,000 hours

Minimum Starting Temp -30°C
 Maximum Operating Temp.....40°C
 CRI..... >+92
 Base E12 & E26
 Warranty..... 3 Years

Specifications:



60W FB11 E26



60W FB11 E12



40W FB11 E26



40W FB11 E12



25W FB11 E26



25W FB11 E12

ITEM #	DESCRIPTION	WATTS	LUMENS	BASE	CCT	CRI	WATT EQUIV.	LIFE	FINISH	MOL.	DIA.
FB11 25W, E12 Base, Dimmable											
FB11D2524E12SCL92	B11 25W 24K E12 CL 92CRI	3.0	250	E12	2400K	92	25	15000	CLEAR	3.8	1.4
FB11D2527E12SCL95	B11 25W 27K E12 CL 95CRI	3.0	250	E12	2700K	95	25	15000	CLEAR	3.8	1.4
FB11D2530E12SCL95	B11 25W 30K E12 CL 95CRI	3.0	250	E12	3000K	95	25	15000	CLEAR	3.8	1.4
FB11D2540E12SCL95	B11 25W 40K E12 CL 95CRI	3.0	250	E12	4000K	95	25	15000	CLEAR	3.8	1.4
FB11D2550E12SCL95	B11 25W 50K E12 CL 95CRI	3.0	250	E12	5000K	95	25	15000	CLEAR	3.8	1.4
FB11 25W, E26 Base, Dimmable											
FB11D2524E26SCL92	B11 25W 24K E26 CL 92CRI	3.0	250	E26	2400K	92	25	15000	CLEAR	3.5	1.4
FB11D2527E26SCL95	B11 25W 27K E26 CL 95CRI	3.0	250	E26	2700K	95	25	15000	CLEAR	3.5	1.4
FB11D2530E26SCL95	B11 25W 30K E26 CL 95CRI	3.0	250	E26	3000K	95	25	15000	CLEAR	3.5	1.4
FB11D2540E26SCL95	B11 25W 40K E26 CL 95CRI	3.0	250	E26	4000K	95	25	15000	CLEAR	3.5	1.4
FB11D2550E26SCL95	B11 25W 50K E26 CL 95CRI	3.0	250	E26	5000K	95	25	15000	CLEAR	3.5	1.4
FB11 40W, E12 Base, Dimmable											
FB11D4024E12SCL92	B11 40W 24K E12 CL 92CRI	4.0	300	E12	2400K	92	40	15000	CLEAR	3.8	1.4
FB11D4027E12SCL95	B11 40W 27K E12 CL 95CRI	4.0	300	E12	2700K	95	40	15000	CLEAR	3.8	1.4
FB11D4030E12SCL95	B11 40W 30K E12 CL 95CRI	4.0	300	E12	3000K	95	40	15000	CLEAR	3.8	1.4
FB11D4040E12SCL95	B11 40W 40K E12 CL 95CRI	4.0	300	E12	4000K	95	40	15000	CLEAR	3.8	1.4
FB11D4050E12SCL95	B11 40W 50K E12 CL 95CRI	4.0	300	E12	5000K	95	40	15000	CLEAR	3.8	1.4
FB11 40W, E26 Base, Dimmable											
FB11D4024E26SCL92	B11 40W 24K E26 CL 92CRI	4.0	300	E26	2400K	92	40	15000	CLEAR	3.5	1.4
FB11D4027E26SCL95	B11 40W 27K E26 CL 95CRI	4.0	300	E26	2700K	95	40	15000	CLEAR	3.5	1.4
FB11D4030E26SCL95	B11 40W 30K E26 CL 95CRI	4.0	300	E26	3000K	95	40	15000	CLEAR	3.5	1.4
FB11D4040E26SCL95	B11 40W 40K E26 CL 95CRI	4.0	300	E26	4000K	95	40	15000	CLEAR	3.5	1.4
FB11D4050E26SCL95	B11 40W 50K E26 CL 95CRI	4.0	300	E26	5000K	95	40	15000	CLEAR	3.5	1.4
FB11 60W, E12 Base, Dimmable											
FB11D6024E12SCL92	B11 60W 24K E12 CL 92CRI	5.0	500	E12	2400K	92	60	15000	CLEAR	3.8	1.4
FB11D6027E12SCL95	B11 60W 27K E12 CL 95CRI	5.0	500	E12	2700K	95	60	15000	CLEAR	3.8	1.4
FB11D6030E12SCL95	B11 60W 30K E12 CL 95CRI	5.0	500	E12	3000K	95	60	15000	CLEAR	3.8	1.4
FB11D6040E12SCL95	B11 60W 40K E12 CL 95CRI	5.0	500	E12	4000K	95	60	15000	CLEAR	3.8	1.4
FB11D6050E12SCL95	B11 60W 50K E12 CL 95CRI	5.0	500	E12	5000K	95	60	15000	CLEAR	3.8	1.4
FB11 60W, E26 Base, Dimmable											
FB11D6024E26SCL92	B11 60W 24K E26 CL 92CRI	5.0	500	E26	2400K	92	60	15000	CLEAR	3.5	1.4
FB11D6027E26SCL95	B11 60W 27K E26 CL 95CRI	5.0	500	E26	2700K	95	60	15000	CLEAR	3.5	1.4
FB11D6030E26SCL95	B11 60W 30K E26 CL 95CRI	5.0	500	E26	3000K	95	60	15000	CLEAR	3.5	1.4
FB11D6040E26SCL95	B11 60W 40K E26 CL 95CRI	5.0	500	E26	4000K	95	60	15000	CLEAR	3.5	1.4
FB11D6050E26SCL95	B11 60W 50K E26 CL 95CRI	5.0	500	E26	5000K	95	60	15000	CLEAR	3.5	1.4

Specifications:



60W FA19



40W FA19

ITEM #	DESCRIPTION	WATTS	LUMENS	BASE	CCT	CRI	WATT EQUIV.	LIFE	FINISH	MOL	DIA.
FA19 40W, E26 Base, Dimmable											
FA19D4024E26SCL92	A19 40W 24K E26 CL 92CRI	4.5	450	E26	2400K	92	40	15000	CLEAR	4.2	3.4
FA19D4027E26SCL95	A19 40W 27K E26 CL 95CRI	4.5	450	E26	2700K	95	40	15000	CLEAR	4.2	3.4
FA19D4030E26SCL95	A19 40W 30K E26 CL 95CRI	4.5	450	E26	3000K	95	40	15000	CLEAR	4.2	3.4
FA19D4040E26SCL95	A19 40W 40K E26 CL 95CRI	4.5	450	E26	4000K	95	40	15000	CLEAR	4.2	3.4
FA19D4050E26SCL95	A19 40W 50K E26 CL 95CRI	4.5	450	E26	5000K	95	40	15000	CLEAR	4.2	3.4
FA19 60W, E26 Base, Dimmable											
FA19D6024E26SCL92	A19 60W 24K E26 CL 92CRI	8.0	800	E26	2400K	92	60	15000	CLEAR	4.2	3.4
FA19D6027E26SCL95	A19 60W 27K E26 CL 95CRI	8.0	800	E26	2700K	95	60	15000	CLEAR	4.2	3.4
FA19D6030E26SCL95	A19 60W 30K E26 CL 95CRI	8.0	800	E26	3000K	95	60	15000	CLEAR	4.2	3.4
FA19D6040E26SCL95	A19 60W 40K E26 CL 95CRI	8.0	800	E26	4000K	95	60	15000	CLEAR	4.2	3.4
FA19D6050E26SCL95	A19 60W 50K E26 CL 95CRI	8.0	800	E26	5000K	95	60	15000	CLEAR	4.2	3.4

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high-quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market, that transforms your surroundings and envelopes you in warmth. Lighting that generates beauty with every flip of the switch.