



Allusion LED Line with Smooth Warm Dimming

Introducing TCP's latest offering of Allusion LED Line—the "incandescent-like" LEDs that offer a unique dimming profile, replicating true incandescent/halogen dimming.

Reasons to choose the Allusion LED Lamps from TCP

- Instant energy savings - up to 85% more efficient than incandescent/halogen replacements
- Long-life of 25,000/30,000 (SL16) hours minimizes replacement and maintenance costs
- Smooth warm dimming creates the perfect atmosphere
- UL approved for damp locations* - can be used outdoors when protected from elements. Can withstand humidity indoors/outdoors
- Shatter resistance lowers the risk of injury and breakage

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Decorative
- Track Lights
- Recessed Downlights

Specifications

Voltage 120VAC/ 12 VAC (MR16)
Input Line Frequency..... 50/60Hz
Lamp Life (Rated)25,000/30,000 (SL16)
Minimum Starting Temp-22°F/-30°C
Maximum Operating Temp.....45°C

CRI 80
Color Temperatures 3000K to 2000K/
..... 3000K to 1800K (MR16/DL)/

Specifications



BR30



PAR38
40°/25°
Beam Angles



PAR30
40°/25°
Beam Angles



MR16 GU5.3
20°
Beam Angle



**5 5/8" Recessed
Downlight**

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	COLOR TEMPERATURE	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED BR30 65W Equivalent												
LED10BR30DA	LED 10W BR30 27K Allusion	120V	10	65	675	67.5	>80	3000K to 2000K	-	5.4	3.8	E26
LED PAR38 90W Equivalent												
L15P38DFLA	LED 15W PAR38 30K Allusion FL	120V	12.5	90	975	78.00	>80	3000K to 2000K	40°	5.4	4.75	E26
LED PAR30 90W Equivalent												
L15P30DFLA	LED 15W PAR30 30K Allusion FL	120V	12.5	90	950	76.00	>80	3000K to 2000K	40°	4.7	3.8	E26
LED MR16 35W Equivalent												
L712VMR16DNFLA	LED 7W MR16 30K Allusion NFL	12V	6	35	350	58.33	>80	3000K to 1800K	20°	1.9	2.0	E26
LED 5 5/8" Downlight 65W Equivalent												
LED10DR56DA	LED 11W 5 5/8" Recessed Downlight Allusion	120V	11	65	1100	100	>80	3000K to 1800K	-	3.0	7.5	E26

Dimmer Compatibility

E26 SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	R50-IPLO6-10M
	R61-06674-POI
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DWVCL-153PH-WH

MR16 SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	Sureslide 6615P
Lutron	Diva DVLV-600P
	Divs DVELV-300P
	Skylark SLEV-300P
	Skylark SLV-600P
	Nova NELV-450
	Nova NTELV-600
	MALV-600
	VERTI VTELV-600M
Cooper	DAL06P - All load dimmer
	SAL06P

For the most up-to-date specs, please visit www.tcp.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP SEP 2026/WF225757



PAR38 and PAR30
lamps UL approved
for wet location



RoHS
COMPLIANT

5 YEAR
WARRANTY

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516