



Horticulture LED Vapor Tight Product Specifications



The TCP LED HVT Series Horticulture Vapor Tight features a lightweight 4FT design to support both the flowering and growth stages of plant development. This durable, 45° C rated fixture efficiently delivers up to 289 $\mu\text{mol/s}$ of photosynthetic photon flux while maximizing energy savings due to an efficacy of up to 2.71 $\mu\text{mol/J}$. The long 50,000 hour rated life significantly decreases maintenance, labor, and material costs over the life of the fixture.

Reasons to choose the LED HVT Series Vapor Tight from TCP

- High efficacy: up to 2.71 $\mu\text{mol/J}$
- Powerful 289 $\mu\text{mol/s}$ photosynthetic photon flux
- Instant-on, no warm up time for full light
- Long-life: 50,000 hours
- Durable light weight plastic housing
- IP65 rating prevents dirt and grime build up behind fixture lens
- Factory installed SmartStuff SmartBox option

Ideal Applications:

- T5 & T8 Grow Light Replacements
- High Pressure Sodium Replacements
- Metal Halide Replacements
- Vertical Farms
- Grow Tents
- Supplemental Growth Lighting



Horticulture LED Vapor Tight


Specifications

Input Line Voltage 120-277 VAC
Input Line Frequency (Hz)..... 50/60HZ
Wattage (W)..... 100W
Photosynthetic Photon Efficacy (PPF)..... $\leq 2.71 \mu\text{mol/J}$
Rated Life..... 50,000 hours
Minimum Starting Temperature -40°C (-40°F)
Maximum Operating Temperature..... 45°C (113°F)
Power Factor >0.90
THD..... <20%
Ratings cULus wet location rated, IP65
Controls..... 0-10V dimming (standard)




The Power of TCP SmartStuff

- Easily schedule day and night cycles.
- Save multiple scenes to your account to provide the optimum PPF levels for each plant type. No need to adjust your light mounting height.
- Factory installed, no need for expensive control wiring.
- Bluetooth controlled, no WiFi required.
- Safe and secure. Lights are locked into your account once programmed.




Available Spectrums:

All Purpose Growth Spectrum (Item #: HVT4UZDA3VG)



ITEMS	MEASURED VALUE	UNIT
PPF (400-700nm)	191.18	$\mu\text{mol/s}$
PPF (400-500nm)	46.16	$\mu\text{mol/s}$
PPF (500-600nm)	65.61	$\mu\text{mol/s}$
PPF (600-700nm)	80.52	$\mu\text{mol/s}$
PPE	1.92	$\mu\text{mol/J}$
PF _{FR}	3.10	$\mu\text{mol/s}$

Supplemental Growth Spectrum (Item #: HVT4UZDA3FL)



ITEMS	MEASURED VALUE	UNIT
PPF (400-700nm)	289.34	$\mu\text{mol/s}$
PPF (400-500nm)	19.14	$\mu\text{mol/s}$
PPF (500-600nm)	7.09	$\mu\text{mol/s}$
PPF (600-700nm)	263.27	$\mu\text{mol/s}$
PPE	2.71	$\mu\text{mol/J}$
PF _{FR}	1.16	$\mu\text{mol/s}$



Horticulture LED Vapor Tight

Applications

The TCP LED HVT Series Horticulture Vapor Tight is a low cost option for mid-level to commercial horticulture applications. Benefits include high efficiency, up to 289 $\mu\text{mol/s}$ of photosynthetic photon flux, long-life, instant-on, and a simple 4FT vapor tight design that can be used in a variety of horticulture lighting applications.

Construction

- Durable, light weight plastic body
- Clear polycarbonate lens
- 4' length provides a large swathe of PPFD

Electrical

- cULus wet location rated
- 0-10V dimming driver (standard)
- Easy-to-access wiring compartment
- System rated for long 50,000 hour life
- Efficiently delivers up to 2.71 $\mu\text{mol/J}$

Optics

- High impact, clear acrylic lens comes standard to protect the LEDs and minimize glare

Item Number

Notes

Type



Listings

UL/cUL Listed
RoHS Compliant

Warranty

Five year limited warranty against defects in manufacturing.

Catalog Ordering Matrix

Example: HVT4UZDA3VG

HVT	4	U	ZD	A3			
FAMILY	LENGTH	VOLTAGE	CONTROLS/DIMMING	WATTAGE ¹	SPECTRUM	FACTORY INSTALLED OPTIONS	POWER CORD OPTION
HVT – Horticultural Vapor Tight	4 – 4FT	U – 120-277V	ZD – 0-10V Dimming	A3 – 100W	VG – All Purpose Growth FL – Supplemental Growth	Blank - No SmartBox	Blank - No Cord, Direct Wire


¹ Actual wattage may differ by +/- 10%

Field Installed Accessories

ITEM NUMBER	DESCRIPTION
EZHANGER	10FT Cable Hanging Kit (1 kit needed per unit)



For the most up-to-date specs and warranty information, please visit www.tcpi.com

Product Dimensions:




Product Installation:

Hang Installation:



EZHANGER add on accessory shown

Surface Mount Installation:



Surface mount clip included standard in box

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516