



Elite Series PAR Lamps Black Housing

Product Specifications



Introducing an additional option to our award-winning PAR portfolio, Elite Series PAR Lamps with Black Housing are now available.

Reasons to choose the Elite Series PAR Lamps from TCP

- Energy Efficient: Up to 85% less energy than halogen replacements
- Smooth, uniform dimming
- Long Life: 25,000 hours
- 120W, 90W, 75W, 60W and 50W replacements
- Smooth black outer housing seamlessly blends into lighting applications
- Excellent color consistency and high color rendering (CRI)
- Available in 2400K, 2700K, 3000K, 3500K, 4100K and 5000K

Ideal Applications

- Track Lights
- Recessed Downlights
- Display Lights
- Outdoor fixtures that protect lamps from the elements

Specifications:

Voltage 120V
Wattage..... 8, 10, 12, 14, 17
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 25,000 hours
Minimum Starting Temp -30°C
Maximum Operating Temp..... 40°C

Color Temperature 2400K, 2700K, 3000K,
3500K, 4100K, 5000K
CRI 80
Beam Angle 15°, 25°, 40°
Base E26
Warranty 5 Years

Specifications:



PAR38



PAR30



PAR30SN



PAR20

ITEM #	DESCRIPTION	VOLTAGE	WATTS	REPLACEMENT WATTS	LUMENS	LPW	CBCP	BEAM ANGLE	CCT	CRI	MOL (inches)	DIA (inches)	CASE QTY	STK/ MTO
PAR38 Lamps – Dimmable • 25,000 Hours														
LED17P38D24KFLB	Dimmable 17W Smooth PAR38 - 2400K 40°, Black	120	17	120	1200	70.6	2132	40	2400K	80	5.3	4.8	12	MTO
LED17P38D27KFLB	Dimmable 17W Smooth PAR38 - 2700K 40°, Black	120	17	120	1200	70.6	2563	40	2700K	80	5.3	4.8	12	STK
LED17P38D27KNFLB	Dimmable 17W Smooth PAR38 - 2700K 25°, Black	120	17	120	1200	70.6	5710	25	2700K	80	5.3	4.8	12	STK
LED17P38D27KSPB	Dimmable 17W Smooth PAR38 - 2700K 15°, Black	120	17	90	1200	70.6	8338	15	2700K	80	5.3	4.8	12	MTO
LED17P38D30KFLB	Dimmable 17W Smooth PAR38 - 3000K 40°, Black	120	17	120	1250	73.5	3107	40	3000K	80	5.3	4.8	12	STK
LED17P38D30KNFLB	Dimmable 17W Smooth PAR38 - 3000K 25°, Black	120	17	120	1250	73.5	6130	25	3000K	80	5.3	4.8	12	STK
LED17P38D30KSPB	Dimmable 17W Smooth PAR38 - 3000K 15°, Black	120	17	90	1250	73.5	8658	15	3000K	80	5.3	4.8	12	MTO
LED17P38D35KFLB	Dimmable 17W Smooth PAR38 - 3500K 40°, Black	120	17	120	1275	75	3132	40	3500K	80	5.3	4.8	12	MTO
LED17P38D35KNFLB	Dimmable 17W Smooth PAR38 - 3500K 25°, Black	120	17	120	1275	75	7550	25	3500K	80	5.3	4.8	12	MTO
LED17P38D35KSPB	Dimmable 17W Smooth PAR38 - 3500K 15°, Black	120	17	90	1275	75	8771	15	3500K	80	5.3	4.8	12	MTO
LED17P38D41KFLB	Dimmable 17W Smooth PAR38 - 4100K 40°, Black	120	17	120	1300	76.5	3366	40	4100K	80	5.3	4.8	12	MTO
LED17P38D41KNFLB	Dimmable 17W Smooth PAR38 - 4100K 25°, Black	120	17	120	1300	76.5	7292	25	4100K	80	5.3	4.8	12	MTO
LED17P38D41KSPB	Dimmable 17W Smooth PAR38 - 4100K 15°, Black	120	17	90	1300	76.5	9947	15	4100K	80	5.3	4.8	12	MTO
LED17P38D50KFLB	Dimmable 17W Smooth PAR38 - 5000K 40°, Black	120	17	120	1300	76.5	3183	40	5000K	80	5.3	4.8	12	MTO
LED17P38D50KNFLB	Dimmable 17W Smooth PAR38 - 5000K 25°, Black	120	17	120	1300	76.5	7043	25	5000K	80	5.3	4.8	12	MTO
LED17P38D50KSPB	Dimmable 17W Smooth PAR38 - 5000K 15°, Black	120	17	90	1300	76.5	10989	15	5000K	80	5.3	4.8	12	MTO
LED14P38D27KFLB	Dimmable 14W Smooth PAR38 - 2700K 40°, Black	120	14	90	1050	75	2858	40	2700K	80	5.3	4.8	12	STK
LED14P38D27KNFLB	Dimmable 14W Smooth PAR38 - 2700K 25°, Black	120	14	90	1050	75	5583	25	2700K	80	5.3	4.8	12	STK
LED14P38D27KSPB	Dimmable 14W Smooth PAR38 - 2700K 15°, Black	120	14	90	1050	75	10949	15	2700K	80	5.3	4.8	12	MTO
LED14P38D30KFLB	Dimmable 14W Smooth PAR38 - 3000K 40°, Black	120	14	90	1100	78.6	2846	40	3000K	80	5.3	4.8	12	STK
LED14P38D30KNFLB	Dimmable 14W Smooth PAR38 - 3000K 25°, Black	120	14	90	1100	78.6	6721	25	3000K	80	5.3	4.8	12	STK
LED14P38D30KSPB	Dimmable 14W Smooth PAR38 - 3000K 15°, Black	120	14	90	1100	78.6	11300	15	3000K	80	5.3	4.8	12	MTO
LED14P38D35KFLB	Dimmable 14W Smooth PAR38 - 3500K 40°, Black	120	14	90	1125	80.4	3469	40	3500K	80	5.3	4.8	12	MTO
LED14P38D35KNFLB	Dimmable 14W Smooth PAR38 - 3500K 25°, Black	120	14	90	1125	80.4	6970	25	3500K	80	5.3	4.8	12	MTO
LED14P38D35KSPB	Dimmable 14W Smooth PAR38 - 3500K 15°, Black	120	14	90	1125	80.4	10098	15	3500K	80	5.3	4.8	12	MTO
LED14P38D41KFLB	Dimmable 14W Smooth PAR38 - 4100K 40°, Black	120	14	90	1150	82.1	2612	40	4100K	80	5.3	4.8	12	MTO
LED14P38D41KNFLB	Dimmable 14W Smooth PAR38 - 4100K 25°, Black	120	14	90	1150	82.1	4546	25	4100K	80	5.3	4.8	12	MTO
LED14P38D41KSPB	Dimmable 14W Smooth PAR38 - 4100K 15°, Black	120	14	90	1150	82.1	11718	15	4100K	80	5.3	4.8	12	MTO
LED14P38D50KFLB	Dimmable 14W Smooth PAR38 - 5000K 40°, Black	120	14	90	1150	82.1	4621	40	5000K	80	5.3	4.8	12	MTO
LED14P38D50KNFLB	Dimmable 14W Smooth PAR38 - 5000K 25°, Black	120	14	90	1150	82.1	7611	25	5000K	80	5.3	4.8	12	MTO
LED14P38D50KSPB	Dimmable 14W Smooth PAR38 - 5000K 15°, Black	120	14	90	1150	82.1	12147	15	5000K	80	5.3	4.8	12	MTO



Elite Series PAR Lamps Black Housing

ITEM #	DESCRIPTION	VOLTAGE	WATTS	REPLACEMENT WATTS	LUMENS	LPW	CBCP	BEAM ANGLE	CCT	CRI	MOL (inches)	DIA (inches)	CASE QTY	STK/ MTO
PAR30 Lamps – Dimmable • 25,000 Hours														
LED14P30D24KFLB	Dimmable 14W Smooth PAR30 - 2400K 40°, Black	120	14	75	1050	75	2513	40	2400K	80	4.8	3.8	12	MTO
LED14P30D24KNFLB	Dimmable 14W Smooth PAR30 - 2400K 25°, Black	120	14	75	1050	75	4417	25	2400K	80	4.8	3.8	12	MTO
LED14P30D27KFLB	Dimmable 14W Smooth PAR30 - 2700K 40°, Black	120	14	75	1050	75	3021	40	2700K	80	4.8	3.8	12	STK
LED14P30D27KNFLB	Dimmable 14W Smooth PAR30 - 2700K 25°, Black	120	14	75	1050	75	5310	25	2700K	80	4.8	3.8	12	STK
LED14P30D27KSPB	Dimmable 14W Smooth PAR30 - 2700K 15°, Black	120	14	75	1050	75	9033	15	2700K	80	4.8	3.8	12	MTO
LED14P30D30KFLB	Dimmable 14W Smooth PAR30 - 3000K 40°, Black	120	14	75	1100	78.6	2881	40	3000K	80	4.8	3.8	12	STK
LED14P30D30KNFLB	Dimmable 14W Smooth PAR30 - 3000K 25°, Black	120	14	75	1100	78.6	8169	25	3000K	80	4.8	3.8	12	STK
LED14P30D30KSPB	Dimmable 14W Smooth PAR30 - 3000K 15°, Black	120	14	75	1100	78.6	9328	15	3000K	80	4.8	3.8	12	MTO
LED14P30D35KFLB	Dimmable 14W Smooth PAR30 - 3500K 40°, Black	120	14	75	1125	80.4	3196	40	3500K	80	4.8	3.8	12	MTO
LED14P30D41KFLB	Dimmable 14W Smooth PAR30 - 4100K 40°, Black	120	14	75	1150	82.1	3154	40	4100K	80	4.8	3.8	12	MTO
LED14P30D41KNFLB	Dimmable 14W Smooth PAR30 - 4100K 25°, Black	120	14	75	1150	82.1	6813	25	4100K	80	4.8	3.8	12	MTO
LED14P30D41KSPB	Dimmable 14W Smooth PAR30 - 4100K 15°, Black	120	14	75	1150	82.1	9681	15	4100K	80	4.8	3.8	12	MTO
LED14P30D50KFLB	Dimmable 14W Smooth PAR30 - 5000K 40°, Black	120	14	75	1150	82.1	3212	40	5000K	80	4.8	3.8	12	MTO
LED14P30D50KNFLB	Dimmable 14W Smooth PAR30 - 5000K 25°, Black	120	14	75	1150	82.1	5872	25	5000K	80	4.8	3.8	12	MTO
LED14P30D50KSPB	Dimmable 14W Smooth PAR30 - 5000K 15°, Black	120	14	75	1150	82.1	10043	15	5000K	80	4.8	3.8	12	MTO
LED12P30D27KFLB	Dimmable 12W Smooth PAR30 - 2700K 40°, Black	120	12	75	850	70.8	1924	40	2700K	80	4.8	3.8	12	STK
LED12P30D27KNFLB	Dimmable 12W Smooth PAR30 - 2700K 25°, Black	120	12	75	850	70.8	5473	25	2700K	80	4.8	3.8	12	STK
LED12P30D27KSPB	Dimmable 12W Smooth PAR30 - 2700K 15°, Black	120	12	75	850	70.8	8402	15	2700K	80	4.8	3.8	12	MTO
LED12P30D30KFLB	Dimmable 12W Smooth PAR30 - 3000K 40°, Black	120	12	75	875	72.9	2596	40	3000K	80	4.8	3.8	12	STK
LED12P30D30KNFLB	Dimmable 12W Smooth PAR30 - 3000K 25°, Black	120	12	75	875	72.9	5523	25	3000K	80	4.8	3.8	12	STK
LED12P30D30KSPB	Dimmable 12W Smooth PAR30 - 3000K 15°, Black	120	12	75	875	72.9	8437	15	3000K	80	4.8	3.8	12	MTO
LED12P30D35KFLB	Dimmable 12W Smooth PAR30 - 3500K 40°, Black	120	12	75	900	75	2608	40	3500K	80	4.8	3.8	12	MTO
LED12P30D41KFLB	Dimmable 12W Smooth PAR30 - 4100K 40°, Black	120	12	75	925	77.1	2759	40	4100K	80	4.8	3.8	12	MTO
LED12P30D41KNFLB	Dimmable 12W Smooth PAR30 - 4100K 25°, Black	120	12	75	925	77.1	6017	25	4100K	80	4.8	3.8	12	MTO
LED12P30D41KSPB	Dimmable 12W Smooth PAR30 - 4100K 15°, Black	120	12	75	925	77.1	7275	15	4100K	80	4.8	3.8	12	MTO
LED12P30D50KFLB	Dimmable 12W Smooth PAR30 - 5000K 40°, Black	120	12	75	950	79.2	2235	40	5000K	80	4.8	3.8	12	MTO
LED12P30D50KNFLB	Dimmable 12W Smooth PAR30 - 5000K 25°, Black	120	12	75	950	79.2	4088	25	5000K	80	4.8	3.8	12	MTO
LED12P30D50KSPB	Dimmable 12W Smooth PAR30 - 5000K 15°, Black	120	12	75	950	79.2	7375	15	5000K	80	4.8	3.8	12	MTO
PAR30 Short Neck Lamps – Dimmable • 25,000 Hours														
LED12P30SD27KFLB	Dimmable 12W Smooth PAR30 Short Neck - 2700K 40°, Black	120	12	75	850	70.8	2261	40	2700K	80	3.5	3.8	12	STK
LED12P30SD27KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 2700K 25°, Black	120	12	75	850	70.8	4333	25	2700K	80	3.5	3.8	12	STK
LED12P30SD27KSPB	Dimmable 12W Smooth PAR30 Short Neck - 2700K 15°, Black	120	12	75	850	70.8	7274	15	2700K	80	3.5	3.8	12	MTO
LED12P30SD30KFLB	Dimmable 12W Smooth PAR30 Short Neck - 3000K 40°, Black	120	12	75	875	72.9	2349	40	3000K	80	3.5	3.8	12	STK
LED12P30SD30KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 3000K 25°, Black	120	12	75	875	72.9	5630	25	3000K	80	3.5	3.8	12	STK
LED12P30SD30KSPB	Dimmable 12W Smooth PAR30 Short Neck - 3000K 15°, Black	120	12	75	875	72.9	7705	15	3000K	80	3.5	3.8	12	MTO
LED12P30SD35KFLB	Dimmable 12W Smooth PAR30 Short Neck - 3500K 40°, Black	120	12	75	900	75	2032	40	3500K	80	3.5	3.8	12	MTO
LED12P30SD35KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 3500K 25°, Black	120	12	75	900	75	5832	25	3500K	80	3.5	3.8	12	MTO
LED12P30SD41KFLB	Dimmable 12W Smooth PAR30 Short Neck - 4100K 40°, Black	120	12	75	925	77.1	2235	40	4100K	80	3.5	3.8	12	MTO
LED12P30SD41KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 4100K 25°, Black	120	12	75	925	77.1	7159	25	4100K	80	3.5	3.8	12	MTO
LED12P30SD41KSPB	Dimmable 12W Smooth PAR30 Short Neck - 4100K 15°, Black	120	12	75	925	77.1	7768	15	4100K	80	3.5	3.8	12	MTO
LED12P30SD50KFLB	Dimmable 12W Smooth PAR30 Short Neck - 5000K 40°, Black	120	12	75	950	79.2	2500	40	5000K	80	3.5	3.8	12	MTO
LED12P30SD50KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 5000K 25°, Black	120	12	75	950	79.2	4792	25	5000K	80	3.5	3.8	12	MTO
LED12P30SD50KSPB	Dimmable 12W Smooth PAR30 Short Neck - 5000K 15°, Black	120	12	75	950	79.2	8045	15	5000K	80	3.5	3.8	12	MTO



Elite Series PAR Lamps Black Housing

ITEM #	DESCRIPTION	VOLTAGE	WATTS	REPLACEMENT WATTS	LUMENS	LPW	CBCP	BEAM ANGLE	CCT	CRI	MOL (inches)	DIA (inches)	CASE QTY	STK/ MTO
PAR30 Short Neck Lamps (cont.)														
LED10P30SD27KFLB	Dimmable 10W Smooth PAR30 Short Neck - 2700K 40°, Black	120	10	60	700	70	2060	40	2700K	80	3.5	3.8	12	STK
LED10P30SD27KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 2700K 25°, Black	120	10	60	700	70	4427	25	2700K	80	3.5	3.8	12	STK
LED10P30SD27KSPB	Dimmable 10W Smooth PAR30 Short Neck - 2700K 15°, Black	120	10	60	700	70	7408	15	2700K	80	3.5	3.8	12	MTO
LED10P30SD30KFLB	Dimmable 10W Smooth PAR30 Short Neck - 3000K 40°, Black	120	10	60	725	72.5	2173	40	3000K	80	3.5	3.8	12	STK
LED10P30SD30KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 3000K 25°, Black	120	10	60	725	72.5	4799	25	3000K	80	3.5	3.8	12	STK
LED10P30SD30KSPB	Dimmable 10W Smooth PAR30 Short Neck - 3000K 15°, Black	120	10	60	725	72.5	8181	15	3000K	80	3.5	3.8	12	MTO
LED10P30SD35KFLB	Dimmable 10W Smooth PAR30 Short Neck - 3500K 40°, Black	120	10	60	750	75	2289	40	3500K	80	3.5	3.8	12	MTO
LED10P30SD35KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 3500K 25°, Black	120	10	60	750	75	4927	25	3500K	80	3.5	3.8	12	MTO
LED10P30SD41KFLB	Dimmable 10W Smooth PAR30 Short Neck - 4100K 40°, Black	120	10	60	775	77.5	1894	40	4100K	80	3.5	3.8	12	MTO
LED10P30SD41KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 4100K 25°, Black	120	10	60	775	77.5	5539	25	4100K	80	3.5	3.8	12	MTO
LED10P30SD41KSPB	Dimmable 10W Smooth PAR30 Short Neck - 4100K 15°, Black	120	10	60	775	77.5	7127	15	4100K	80	3.5	3.8	12	MTO
LED10P30SD50KFLB	Dimmable 10W Smooth PAR30 Short Neck - 5000K 40°, Black	120	10	60	800	80	2432	40	5000K	80	3.5	3.8	12	MTO
LED10P30SD50KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 5000K 25°, Black	120	10	60	800	80	5844	25	5000K	80	3.5	3.8	12	MTO
LED10P30SD50KSPB	Dimmable 10W Smooth PAR30 Short Neck - 5000K 15°, Black	120	10	60	800	80	7717	15	5000K	80	3.5	3.8	12	MTO
PAR20 Lamps – Dimmable • 25,000 Hours														
LED8P20D27KFLB	Dimmable 8W Smooth PAR20 - 2700K 40°, Black	120	8	50	575	71.9	1210	40	2700K	80	3.5	2.5	12	STK
LED8P20D27KNFLB	Dimmable 8W Smooth PAR20 - 2700K 25°, Black	120	8	50	575	71.9	2336	25	2700K	80	3.5	2.5	12	STK
LED8P20D30KFLB	Dimmable 8W Smooth PAR20 - 3000K 40°, Black	120	8	50	600	75	1416	40	3000K	80	3.5	2.5	12	STK
LED8P20D30KNFLB	Dimmable 8W Smooth PAR20 - 3000K 25°, Black	120	8	50	600	75	2463	25	3000K	80	3.5	2.5	12	STK
LED8P20D41KFLB	Dimmable 8W Smooth PAR20 - 4100K 40°, Black	120	8	50	650	81.2	1327	40	4100K	80	3.5	2.5	12	STK
LED8P20D41KNFLB	Dimmable 8W Smooth PAR20 - 4100K 25°, Black	120	8	50	650	81.2	2291	25	4100K	80	3.5	2.5	12	STK
LED8P20D50KFLB	Dimmable 8W Smooth PAR20 - 5000K 40°, Black	120	8	50	675	84.4	1501	40	5000K	80	3.5	2.5	12	STK
LED8P20D450KNFLB	Dimmable 8W Smooth PAR20 - 5000K 25°, Black	120	8	50	675	84.4	2059	25	5000K	80	3.5	2.5	12	STK

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP MAY 2023/WF23364



RoHS
COMPLIANT

5 YEAR
WARRANTY

*Based on 12 hours
use per day

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 30 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516