



# LED Filament High CRI Standard Lamps

## Product Specifications



TCP's LED Filament High CRI Standard Lamps combine the beauty and style of traditional lamps with visual aesthetics of exposed filaments and superior LED energy savings. Exclusive technology provides unmatched longevity and perfect dimming down to 5%. High CRI output provides outstanding color consistency and beautiful, natural color rendering.

### Reasons to choose the LED Filament High CRI Standard Lamps from TCP

- High CRI value provides excellent color rendering results and color consistency while maintaining uniformity
- Uses up to 85% less energy than halogen and incandescent lamps
- UL approved for damp and enclosed fixtures
- 15,000 hour rated life and low heat generation reduce replacement and maintenance costs
- ANSI construction compliant means lamps fit most general applications
- Smooth, uniform dimming down to 5%
- All-glass construction

### Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Recessed Lighting

### Specifications

Color Temperatures.....2700K, 3000K, 4000K, 5000K  
Input Line Voltage ..... 120 VAC  
Frequency ..... 50/60HZ  
Lamp Life (Rated) ..... 15,000 hours  
Minimum Starting Temp ..... -30°C

### Item Number Key

1 2 3 4 5 6 7 8 9  
F | A19 | D | 40 | 27 | E26 | S | CL | 95

- 1. Lamp Type: Filament (F)
- 2. Lamp Shape: A19, ST19, T06, T10
- 3. Dimming/Non Dimming: D, N
- 4. Incand. Wattage: 25, 40, 60
- 5. Color Temp: 27, 30, 40, 50
- 6. Base: E12, E26
- 7. Filament Type: Straight (S)
- 8. Finish: Clear (CL), Frost (FR)
- 9. CRI: 95

Maximum Operating Temp ..... 40°C  
CRI ..... 95  
Base ..... E12, E26  
Warranty ..... 3 Years

## Specifications



25W FA15 CLEAR



25W FA15 FROST



40W FA19 CLEAR



40W FA19 FROST



60W FA19 CLEAR



60W FA19 FROST

ITEM #	DESCRIPTION	WATTS	LUMENS	BASE	CCT	CRI	WATT EQUIV.	FINISH	MOL	DIA.	CASE QTY
<b>FA15 25W, E26 Base, Dimmable</b>											
FA15D2527E26SCL95	A19 25W 27K E26 CLEAR 95CRI	3.5	250	E26	2700K	92	25	CLEAR	3.4	3.4	12
FA15D2527E26SFR95	A19 25W 27K E26 FROST 95CRI	3.5	250	E26	2700K	95	25	FROST	3.4	3.4	12
FA15D2550E26SCL95	A19 25W 50K E26 CLEAR 95CRI	3.5	250	E26	5000K	95	25	CLEAR	3.4	3.4	12
FA15D2550E26SFR95	A19 25W 50K E26 FROST 95CRI	3.5	250	E26	5000K	95	25	FROST	3.4	3.4	12
<b>FA19 40W, E26 Base, Dimmable</b>											
FA19D4027E26SCL95	A19 40W 27K E26 CLEAR 95CRI	4.5	450	E26	2700K	92	40	CLEAR	4.2	3.4	12
FA19D4027E26SFR95	A19 40W 27K E26 FROST 95CRI	4.5	450	E26	2700K	95	40	FROST	4.2	3.4	12
FA19D4030E26SCL95	A19 40W 30K E26 CLEAR 95CRI	4.5	450	E26	3000K	95	40	CLEAR	4.2	3.4	12
FA19D4030E26SFR95	A19 40W 30K E26 FROST 95CRI	4.5	450	E26	3000K	95	40	FROST	4.2	3.4	12
FA19D4040E26SCL95	A19 40W 40K E26 CLEAR 95CRI	4.5	450	E26	4000K	95	40	CLEAR	4.2	3.4	12
FA19D4040E26SFR95	A19 40W 40K E26 FROST 95CRI	4.5	450	E26	4000K	95	40	FROST	4.2	3.4	12
FA19D4050E26SCL95	A19 40W 50K E26 CLEAR 95CRI	4.5	450	E26	5000K	95	40	CLEAR	4.2	3.4	12
FA19D4050E26SFR95	A19 40W 50K E26 FROST 95CRI	4.5	450	E26	5000K	95	40	FROST	4.2	3.4	12
<b>FA19 60W, E26 Base, Dimmable</b>											
FA19D6027E26SCL95	A19 60W 27K E26 CLEAR 95CRI	8.0	800	E26	2700K	92	60	CLEAR	4.2	3.4	12
FA19D6027E26SFR95	A19 60W 27K E26 FROST 95CRI	8.0	800	E26	2700K	95	60	FROST	4.2	3.4	12
FA19D6030E26SCL95	A19 60W 30K E26 CLEAR 95CRI	8.0	800	E26	3000K	95	60	CLEAR	4.2	3.4	12
FA19D6030E26SFR95	A19 60W 30K E26 FROST 95CRI	8.0	800	E26	3000K	95	60	FROST	4.2	3.4	12
FA19D6040E26SCL95	A19 60W 40K E26 CLEAR 95CRI	8.0	800	E26	4000K	95	60	CLEAR	4.2	3.4	12
FA19D6040E26SFR95	A19 60W 40K E26 FROST 95CRI	8.0	800	E26	4000K	95	60	FROST	4.2	3.4	12
FA19D6050E26SCL95	A19 60W 50K E26 CLEAR 95CRI	8.0	800	E26	5000K	95	60	CLEAR	4.2	3.4	12
FA19D6050E26SFR95	A19 60W 50K E26 FROST 95CRI	8.0	800	E26	5000K	95	60	FROST	4.2	3.4	12

## Specifications



40W ST19 CLEAR



40W ST19 FROST



25W T06 CLEAR



25W T06 FROST



25W T10 CLEAR



25W T10 FROST

ITEM #	DESCRIPTION	WATTS	LUMENS	BASE	CCT	CRI	WATT EQUIV.	FINISH	MOL	DIA.	CASE QTY
<b>ST19 40W, E26 Base, Dimmable</b>											
FST19D4027E26SCL95	ST19 40W 27K E26 CLEAR 95CRI	5.0	450	E26	2700K	95	40	CLEAR	5.4	2.5	12
FST19D4027E26SFR95	ST19 40W 27K E26 FROST 95CRI	5.0	450	E26	2700K	95	40	FROST	5.4	2.5	12
FST19D4030E26SCL95	ST19 40W 30K E26 CLEAR 95CRI	5.0	450	E26	3000K	95	40	CLEAR	5.4	2.5	12
FST19D4030E26SFR95	ST19 40W 30K E26 FROST 95CRI	5.0	450	E26	3000K	95	40	FROST	5.4	2.5	12
FST19D4040E26SCL95	ST19 40W 40K E26 CLEAR 95CRI	5.0	450	E26	4000K	95	40	CLEAR	5.4	2.5	12
FST19D4040E26SFR95	ST19 40W 40K E26 FROST 95CRI	5.0	450	E26	4000K	95	40	FROST	5.4	2.5	12
FST19D4050E26SCL95	ST19 40W 50K E26 CLEAR 95CRI	5.0	450	E26	5000K	95	40	CLEAR	5.4	2.5	12
FST19D4050E26SFR95	ST19 40W 50K E26 FROST 95CRI	5.0	450	E26	5000K	95	40	FROST	5.4	2.5	12
<b>T06 25W, E12 Base, Dimmable</b>											
FT0603D2527EE12CL95	T06 25W 27K E12 CLEAR 95CRI	3.0	200	E12	2700K	95	25	CLEAR	3.3	0.8	12
FT0603D2527EE12FR95	T06 25W 27K E12 FROST 95CRI	3.0	200	E12	2700K	95	25	FROST	3.3	0.8	12
<b>T10 25W, E26 Base, Dimmable</b>											
FT1005D2527E26SCL95	T10 25W 27K E26 CLEAR 95CRI	3.0	250	E26	2700K	95	25	CLEAR	5.4	1.2	12
FT1005D2527E26SFR95	T10 25W 27K E26 FROST 95CRI	3.0	250	E26	2700K	95	25	FROST	5.4	1.2	12
FT1005D2530E26SCL95	T10 25W 30K E26 CLEAR 95CRI	3.0	250	E26	3000K	95	25	CLEAR	5.4	1.2	12
FT1005D2530E26SFR95	T10 25W 30K E26 FROST 95CRI	3.0	250	E26	3000K	95	25	FROST	5.4	1.2	12

SUGGESTED DIMMER COMPATIBILITY	
MANUFACTURER	MODEL NUMBER
Leviton	R50-IPL06-10M
	R61-06674-POI
Lutron	CTCL-153PDH-WH
	TGCL-153PH-WH
	DVWCL-153PH-WH

Note: E26 compatible dimmer

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

**TCP®**  
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP MAY 2025/WF266000



**RoHS**  
COMPLIANT

**3 YEAR**  
WARRANTY  
\*Based on 12 hours use per day

# TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcpi.com](http://tcpi.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516