



LED Selectable Commercial Recessed Downlights

(Lens Version)

Color & Wattage Selectable Product Specifications



TCP's Selectable Commercial Recessed Downlights offer choices for color temperatures and wattages, making these adaptable for many situations.

Reasons to choose LED Commercial Recessed Downlights from TCP

- 3 Selectable Wattages
- 5 Selectable Colors (30K/35K/41K) (27K/50K)
- Lens Version provides 10% more delivered lumens
- 50,000 hours life minimizes replacement and maintenance costs
- Flicker Free Design for consistent lighting
- Mounts directly to ceiling: 4, 6, 8, 10 or 12 inch
- Shatter resistant
- Matte Silver Finish
- Easy installation and integrated trim
- Snap clips allow for installation without a recessed can
- 85° beam angle (4"/6"/8"/10")
- 70° beam angle (12")
- Smooth, uniform dimming from 100 - 5%

Ideal Applications

- Commercial
- Industrial
- Retail
- Healthcare

Specifications:

Color Temperatures..... 2700K, 3000K, 3500K, 4100K, 5000K
 Wattage options 4" (7/9/12W), (6" (8/10/15W),
 8" (11/15/19W), 10" (18/23/30W),
 12" (18/23/30W)
 Input Line Voltage 120-277V
 Input Line Frequency..... 50/60HZ
 Dimming..... 0-10V

Lamp Life (rated)..... 50,000 hours
 Minimum Starting Temp -22F/-30C
 Maximum Operating Temp..... 104°F/40°C
 CRI..... 80
 IC-rated for direct contact with insulation
 UL approved for damp locations



LED Selectable Commercial Recessed Downlights (Lens Version)

Specifications:



Selectable Commercial Recessed Downlight Lens Version (30K,35K,41K)

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	REPLACEMENT WATTS	LUMENS									LPW	CRI	MOL (inches)	DIA (inches)
					LOWEST WATTAGE			MIDDLE WATTAGE			HIGHEST WATTAGE						
					3000K	3500K	4100K	3000K	3500K	4100K	3000K	3500K	4100K				
4" Selectable Commercial Recessed Downlight Lens Version – 65 Watt Replacement • 50,000 Hour																	
DLC4SWUZLICCT	LED 4" Comm Downlight Lens CCT	120-277V	7/9/12	65	743	765	759	957	990	985	1265	1320	1309	LW:106.1/109.2/108.4 MW:106.3/110/109.4 HW:105.4/110/109.1	80	5	6.2
6" Selectable Commercial Recessed Downlight Lens Version – 85 Watt Replacement • 50,000 Hour																	
DLC6SWUZLICCT	LED 6" Comm Downlight Lens CCT	120-277V	8/10/15	85	902	935	952	1133	1188	1205	1573	1683	1667	LW:112.8/116.9/118.9 MW:113.3/118.8/120.5 HW:104.9/112.2/111.1	80	6.4	7.8
8" Selectable Commercial Recessed Downlight Lens Version – 85 Watt Replacement • 50,000 Hour																	
DLC8SWUZLICCT	LED 8" Comm Downlight Lens CCT	120-277V	11/15/19	85	1397	1430	1436	1892	1876	1953	2294	2365	2294	LW:127/130/130.5 MW:126.1/125/130.2 HW:120.7/124.5/120.7	80	7.4	9.2
10" Selectable Commercial Recessed Downlight Lens Version – 100 Watt Replacement • 50,000 Hour																	
DLC10SWUZLICCT	LED 10" Comm Downlight Lens CCT	120-277V	18/23/30	100	2310	2365	2365	2849	2926	2926	3526	3663	3636	LW:128/131.4/131.4 MW:123.9/127.2/127.2 HW:117.5/122.1/121.2	80	8.25	10.9
12" Selectable Commercial Recessed Downlight Lens Version – 125 Watt Replacement • 50,000 Hour																	
DLC12SWUZLICCT	LED 12" Comm Downlight Lens CCT	120-277V	18/23/30	125	2321	2376	2398	2915	2959	2959	3586	3718	3696	LW:128.9/132/133.2 MW:126.7/128.7/128.7 HW:119.5/123.9/123.2	80	9.5	13



LED Selectable Commercial Recessed Downlights (Lens Version)

Specifications:

Selectable Commercial Recessed Downlight Lens Version (27K,50K)

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	REPLACEMENT WATTS	LUMENS						LPW	CRI	MOL (inches)	DIA (inches)
					LOWEST WATTAGE		MIDDLE WATTAGE		HIGHEST WATTAGE					
					2700K	5000K	2700K	5000K	2700K	5000K				
4" Selectable Commercial Recessed Downlight Lens Version – 65 Watt Replacement • 50,000 Hour														
DLC4SWUZDLCCT2	LED 4" Comm Downlight Lens CCT	120-277V	7/9/12	65	700	750	900	950	1250	1300	LW:100/107.1 MW:100/105.6 HW:104.2/108.3	80	5	6.2
6" Selectable Commercial Recessed Downlight Lens Version – 85 Watt Replacement • 50,000 Hour														
DLC6SWUZDLCCT2	LED 6" Comm Downlight Lens CCT	120-277V	8/10/15	85	900	950	1200	1300	1600	1650	LW:112.5/118.8 MW:120/130 HW:106.7/110	80	6.4	7.8
8" Selectable Commercial Recessed Downlight Lens Version – 85 Watt Replacement • 50,000 Hour														
DLC8SWUZDLCCT2	LED 8" Comm Downlight Lens CCT	120-277V	11/15/19	85	1400	1500	1800	1900	2300	2400	LW:127.3/136.4 MW:120/126.7 HW:121/126.3	80	7.4	9.2
10" Selectable Commercial Recessed Downlight Lens Version – 100 Watt Replacement • 50,000 Hour														
DLC10SWUZDLCCT2	LED 10" Comm Downlight Lens CCT	120-277V	18/23/30	100	1950	2150	2500	2650	3250	3500	LW:108.3/119.4 MW:108.7/115.2 HW:108.3/116.7	80	8.25	10.9
12" Selectable Commercial Recessed Downlight Lens Version – 125 Watt Replacement • 50,000 Hour														
DLC12SWUZDLCCT2	LED 12" Comm Downlight Lens CCT	120-277V	18/23/30	125	1950	2150	2500	2700	3250	3500	LW:108.3/119.4 MW:108.7/117.4 HW:108.3/116.7	80	9.5	13

Optional Accesories

ITEM NUMBER	DESCRIPTION	DIMENSIONS
EMBACKUPCOMDL1	EMERGENCY BACK UP FOR 4" AND 6" SELECTABLE COMMERCIAL DOWNLIGHT	9.45" X 1.77" X 1.18"
EMBACKUPCOMDL2	EMERGENCY BACK UP FOR 8", 10" AND 12" SELECTABLE COMMERCIAL DOWNLIGHT	12.9" X 2.6" X 2.2"



For the most up-to-date specs, please visit www.tpci.com



TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516