



LED Universal Voltage 120-277V Lamps

Product Specifications



TCP's LED Universal Voltage 120-277V Lamps are now available in A-lamps, BR30s, and PAR38s.

Reasons to choose LED Universal Voltage 120-277V Lamps from TCP

- Long life: 25,000 hours minimizes replacement and maintenance costs
- Up to 85% less energy than halogen alternatives
- Excellent color consistency and CRI
- PAR38 lamps are UL approved for wet locations
- Highly durable plastic

Ideal Applications

- Commercial
- Industrial
- Docks
- Warehouses
- Work sites
- Outdoor flood

Specifications:

Input Line Voltage 120-277 VAC
 Input Line Frequency..... 50/60HZ
 Lamp Life (Rated) 25,000 hours
 Minimum Starting Temp -22°F/-30°C

Maximum Operating Temp..... 113°F/45°C
 CRI..... 80
 Warranty..... 5 years





LED Universal Voltage 120-277V Lamps

Specifications:

ITEM #	DESCRIPTION	ENERGY STAR	CBCP	WATTS	LIFE	REPLACEMENT	LUMENS	BEAM ANGLE	CCT	CRI	MOL (inches)	DIA (inches)	BASE	MASTER PACK
23W LED A23 Non Dimmable* - COMING SOON														
L200A23N25UNV27K	LED A23 200W ND 27K 120-277	NO	-	23	25000	200	3000	OMNI	2700K	80	6.3	3.3	E26	12
L200A23N25UNV30K	LED A23 200W ND 30K 120-277	NO	-	23	25000	200	3000	OMNI	3000K	80	6.3	3.3	E26	12
L200A23N25UNV41K	LED A23 200W ND 41K 120-277	NO	-	23	25000	200	3000	OMNI	4100K	80	6.3	3.3	E26	12
L200A23N25UNV50K	LED A23 200W ND 50K 120-277	NO	-	23	25000	200	3000	OMNI	5000K	80	6.3	3.3	E26	12
* Not approved for enclosed luminaires														
18W LED A23 Non Dimmable														
L125A23N25UNV27K	LED 125W A23 UNV 2700K	YES	-	18	25000	125	2000	OMNI	2700K	80	5.8	3.1	E26	12
L125A23N25UNV30K	LED 125W A23 UNV 3000K	NO	-	18	25000	125	2000	OMNI	3000K	80	5.8	3.1	E26	12
L125A23N25UNV40K	LED 125W A23 UNV 4000K	NO	-	18	25000	125	2100	OMNI	4000K	80	5.8	3.1	E26	12
L125A23N25UNV50K	LED 125W A23 UNV 5000K	YES	-	18	25000	125	2200	OMNI	5000K	80	5.8	3.1	E26	12
14W LED A21 Non Dimmable														
L100A21N25UNV27K	LED 14W A21 UNV 2700K	YES	-	14	25000	100	1600	OMNI	2700K	80	5.2	2.8	E26	12
L100A21N25UNV30K	LED 14W A21 UNV 3000K	YES	-	14	25000	100	1625	OMNI	3000K	80	5.2	2.8	E26	12
L100A21N25UNV40K	LED 14W A21 UNV 4000K	YES	-	14	25000	100	1650	OMNI	4000K	80	5.2	2.8	E26	12
L100A21N25UNV50K	LED 14W A21 UNV 5000K	YES	-	14	25000	100	1650	OMNI	5000K	80	5.2	2.8	E26	12
7.5W LED A19 Non Dimmable														
L60A19N25UNV27K	LED 60W A19 UNV 2700K	YES	-	7.5	25000	60	800	OMNI	2700K	80	4.1	2.4	E26	12
L60A19N25UNV30K	LED 60W A19 UNV 3000K	YES	-	7.5	25000	60	800	OMNI	3000K	80	4.1	2.4	E26	12
L60A19N25UNV40K	LED 60W A19 UNV 4000K	YES	-	7.5	25000	60	850	OMNI	4000K	80	4.1	2.4	E26	12
L60A19N25UNV50K	LED 60W A19 UNV 5000K	YES	-	7.5	25000	60	875	OMNI	5000K	80	4.1	2.4	E26	12
9.5W LED BR30 Non Dimmable														
L65BR30N25UNV27K	LED 65W BR30 UNV 2700K	YES	-	9.5	25000	65	900	110°	2700K	80	5.2	3.8	E26	12
L65BR30N25UNV30K	LED 65W BR30 UNV 3000K	YES	-	9.5	25000	65	900	110°	3000K	80	5.2	3.8	E26	12
L65BR30N25UNV40K	LED 65W BR30 UNV 4000K	YES	-	9.5	25000	65	925	110°	4000K	80	5.2	3.8	E26	12
L65BR30N25UNV50K	LED 65W BR30 UNV 5000K	YES	-	9.5	25000	65	1000	110°	5000K	80	5.2	3.8	E26	12
13W LED BR30 Non Dimmable														
L100BR30N25UNV27K	LED 100W BR30 UNV 2700K	YES	-	13	25000	100	1400	110°	2700K	80	5.3	3.6	E26	12
L100BR30N25UNV30K	LED 100W BR30 UNV 3000K	YES	-	13	25000	100	1400	110°	3000K	80	5.3	3.6	E26	12
L100BR30N25UNV40K	LED 100W BR30 UNV 4000K	YES	-	13	25000	100	1450	110°	4000K	80	5.3	3.6	E26	12
L100BR30N25UNV50K	LED 100W BR30 UNV 5000K	YES	-	13	25000	100	1500	110°	5000K	80	5.3	3.6	E26	12
12.5W LED PAR38 Non Dimmable														
L100P38N25UNV27KFL	LED 90W P38 UNV 2700K Fld	YES	2630	12.5	25000	90	1100	40°	2700K	80	5.2	4.8	E26	12
L100P38N25UNV30KFL	LED 90W P38 UNV 3000K Fld	YES	2613	12.5	25000	90	1100	40°	3000K	80	5.2	4.8	E26	12
L100P38N25UNV40KFL	LED 90W P38 UNV 4000K Fld	YES	2532	12.5	25000	90	1150	40°	4000K	80	5.2	4.8	E26	12
L100P38N25UNV50KFL	LED 90W P38 UNV 5000K Fld	YES	2641	12.5	25000	90	1200	40°	5000K	80	5.2	4.8	E26	12
L100P38N25UNV27KNFL	LED 90W P38 UNV 2700K Nar Fld	YES	6245	12.5	25000	90	1100	25°	2700K	80	5.2	4.8	E26	12
L100P38N25UNV30KNFL	LED 90W P38 UNV 3000K Nar Fld	YES	6334	12.5	25000	90	1100	25°	3000K	80	5.2	4.8	E26	12
L100P38N25UNV40KNFL	LED 90W P38 UNV 4000K Nar Fld	YES	6412	12.5	25000	90	1150	25°	4000K	80	5.2	4.8	E26	12
L100P38N25UNV50KNFL	LED 90W P38 UNV 5000K Nar Fld	YES	6572	12.5	25000	90	1200	25°	5000K	80	5.2	4.8	E26	12

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516