



LED Recessed Face Color Selectable Downlights

Product Specifications



For quick, easy, and affordable LED upgrades, switch to TCP's LED Downlights. TCP's Recessed Face Color & Wattage Selectable Downlights have both E26 and direct wire options, PMMA plastic to prevent lens discoloration, and quick-snap holding arms to quickly attach to a recessed can. With a traditional look, these downlights provide smooth, even light in the color temperature you need.

Reasons to choose the LED Recessed Face Color Selectable Downlights from TCP

- Color selectable — choose between 2700K/3000K/3500K or 3000K/4000K/5000K
- Excellent color consistency and CRI enhances colors of the focal point while maintaining uniformity throughout the lighting installation
- Smooth, uniform dimming 100 - 10%
- Long, 50,000 hour life minimizes replacement and maintenance costs
- Very low heat generation makes the downlight perfect for sensitive display lighting
- Durable PMMA plastic housing resists discoloration
- Easy installation — mounts directly to a 4" recessed can and includes both E26 and direct wire power options

Ideal Applications

- Commercial
- Industrial
- Retail
- Residential
- Healthcare

Specifications

Color Temperatures 2700K/3000K/3500K or 3000K/4000K/5000K

Wattage..... 10W

Input Line Voltage 120 VAC

Input Line Frequency..... 50/60HZ

Lamp Life (Rated) 50,000 hours

Minimum Starting Temp-22°F/-30°C

Maximum Operating Temp.....104°F/40°C

CRI.....80

IC-rated for direct contact with insulation

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.



Specifications



4 inch Dimmable Downlight



ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDES. WATTS	LPW	LUMENS	COLOR	MOL CRI	DIA (inches)	BEAM ANGLE	BASE	WARRANTY YEARS	
LED 75W Equivalent Options													
DR4 Downlight • Dimmable • 50,000 Hour													
L75DR4DCCT1	4" LED Recessed Face Color Selectable Downlight 2400/2700/3000	120V	10	75	76.5/85/85	765/850/850	2400K/2700K/3000K	80	3.0	5	120°	E26	5
L75DR4DCCT2	4" LED Recessed Face Color Selectable Downlight 3000/4000/5000	120V	10	75	90/96/91.5	900/960/915	3000K/4000K/5000K	80	3.0	5	120°	E26	5